




裤耳卷切一体、长度一致均匀
Belt loops are integrated with rolling and cutting, ensuring consistent and uniform length.

ZJ2479A 系列/series


高速裤耳绷缝机
HIGH-SPEED BELT LOOP INTERLOCK SEWING MACHINE



前压脚机构专利设计
Patented Design: Front Presser Foot Mechanism



线迹正面
Front side stitch



线迹反面
Back side stitch

ZJ2479A 系列/series

高速裤耳绷缝机

HIGH-SPEED BELT LOOP INTERLOCK SEWING MACHINE



官方订阅号




手机官网



FaceBook



YouTube



Instagram

全球服饰行业设备解决方案运营商
OPERATOR OF EQUIPMENT SOLUTIONS
FOR THE GLOBAL CLOTHING INDUSTRY

针距	针号	针距	针号	针距	针号	针距	针号	针距	针号
ZJ2479A-056M-VF-BD	UY128GAS14#	2	4	5.6	1.4-4.2	1/0.8-1/1.1	6	4000	
ZJ2479A-064M-VF-BD	UY128GAS14#	2	4	6.4	1.4-4.2	1/0.8-1/1.1	6	4000	

056M: 无上装饰线机构, 5.6针位, 标准针板爪; 064M: 无上装饰线机构, 6.4针位, 标准针板爪; BD: 直驱

选配--TK: 砍刀装置

056M: Standard Stitch Mechanism (5.6mm Needle Spacing, Standard Needle Plate Claw), 064M: Standard Stitch Mechanism (6.4mm Needle Spacing, Standard Needle Plate Claw),

BD: Direct Drive System

Optional - TK: Fabric Cutting Device