



E9630/E9640 系列/series

步进智慧罗拉车

STEPPING INTELLIGENT POST-BED SEWING MACHINE



官方订阅号



手机官网



FaceBook



YouTube



Instagram

全球服饰行业设备解决方案运营商
OPERATOR OF EQUIPMENT SOLUTIONS
FOR THE GLOBAL CLOTHING INDUSTRY

ZOJE Eco products



旗舰款
Flagship product



单针(single needle)



双针(double needle)

大针距、三步进、吃厚稳
Large needle gauge, three stepping, strong sewing of thick fabric


厚料机系列
HEAVY DUTY SERIES

E9630/E9640 系列/series

步进智慧罗拉车
STEPPING INTELLIGENT POST-BED SEWING MACHINE




短线头
Short thread



单独电机控制，送料更强劲稳定
Single motor control, more powerful and stable feeding



高清液晶触摸屏
Hd LCD touch screen
高清按键屏（可选）
Hd button screen(optional)



倒缝静音
Reverse stitching mute

E9630-D3-CM/M/ZM/ZH/H/CH-C/B-02-V	0~5.0mm/0~7.0mm	手提7mm/自动8~11mm	Dp x 5 9#-21# Dp x 17 14#-21#	√	3000
E9630-D3D-ZM/ZH-C/B-02-V	0~5.0mm/0~7.0mm	手提7mm/自动8~11mm	Dp x 5 9#-21# Dp x 17 14#-21#	短线头	3000
E9640-D3-M/ZM/ZH-N1.4/N1.8-C/B-02-V	0~5.0mm	手提7mm/自动8~11mm	Dp x 5 9#-21# Dp x 17 14#-21#	√	2000
E9640-D3-H-N1.8/N2.0-C/B-02-V	0~5.0mm	手提7mm/自动8~11mm	Dp x 5 9#-21# Dp x 17 14#-21#	√	2000
E9640-D3-CH-N2.0/2.2/2.4-C/B-02-V	0~5.0mm	手提7mm/自动8~11mm	Dp x 5 9#-21# Dp x 17 14#-21#	√	2000

规格 specification	单针系列 / 双针系列 Single Needle Series/Double Needle Series
加油方式 oil filler Mode	自动供油（旋梭） Auto oil supply(Hook)

缝料类型 Sewing the material type	M: 0.5-1.5mm; H: 1.5-7mm
驱动方式 Drive Mode	电磁铁式+步进驱动 electromagnet mode+Stepper Drive

自动抬压脚 Auto presser foot lifter	√
自动倒缝 Auto back stitch	√

工作电压 Working voltage	220V
额定功率 rated power	750W/850W

CM:超薄料（最大针距4.5mm，11#）；M: 薄料（最大针距4.5mm，14#），配薄料旋梭；ZM: 中厚料（最大针距4.5mm，14#）配M针板+厚料旋梭；H: 厚料（最大针距4.5mm，19#）；ZH: 中厚料（最大针距4.5mm，16#）；CH: 超厚料（最大针距4.5mm，20#）；D3: 单剪线+倒缝+抬压脚；D3D: 短线头单剪线+倒缝+抬压脚；N1.4~N2.4: 双针针间距1.4mm~2.4mm，缺省：单针

CM: Extra Thin Material (Maximum Stitch Length: 4.5mm, Needle Size 11); M: Thin Material (Maximum Stitch Length: 4.5mm, Needle Size 14), equipped with Thin Material Rotary Hook; ZM: Medium-Thick Material (Maximum Stitch Length: 4.5mm, Needle Size 14), equipped with M Throat Plate + Thick Material Rotary Hook; H: Thick Material (Maximum Stitch Length: 4.5mm, Needle Size 19); ZH: Medium-Thick Material (Maximum Stitch Length: 4.5mm, Needle Size 16); CH: Extra Thick Material (Maximum Stitch Length: 4.5mm, Needle Size 20); D3: Single Thread Trimming + Reverse Stitching + Presser Foot Lifting; D3D: Short Thread End Single Thread Trimming + Reverse Stitching + Presser Foot Lifting; N1.4~N2.4: Double Needle (Needle Gauge: 1.4mm~2.4mm); Default: Single Needle