# **マール 中央連進切机** 中国高端缝纫机典范 MODEL OF HIGH-END SEWING MACHINES IN CHINA



## ZJ-740TM 系列/series

曲臂双差动步进剪线四针六线拼缝机

CURVED ARM DOUBLE DIFFERENTIAL STEPPER THREAD-TRIMMING 4-NEEDLE 6-THREAD ASSEMBLING MACHINE

YouTube











全球服饰行业设备解决方案运营商 OPERATOR OF EQUIPMENT SOLUTIONS FOR THE GLOBAL CLOTHING INDUSTRY







一体式机壳、防漏油、适用广 Integrated housing, oil leak prevention, wide applicability

### ZJ-740TM 系列/series

CURVED ARM DOUBLE DIFFERENTIAL STEPPER THREAD-TRIMMING 4-NEEDLE 6-THREAD ASSEMBLING MACHINE



专利防漏油装置,标配高强度纳 米镀层针杆,更耐用 Patented oil-leakage prevention device; standard-equipped with a high-strength nano-plated needle bar for enhanced durability.



全系标配陶瓷过线、出线更顺 畅,线迹更美观 The full product range comes standard with ceramic thread guides, ensuring smoother thread feeding and more attractive stitches.



新型改进式剪线,安全不打手 Newly improved thread trimming mechanism, which is safe and prevents



双差动送料,适应更多特殊面料, 缝纫更平整 Dual differential feeding, which adapts to more special fabric types and delivers

<b>=</b>		<b>1</b>	<b> </b>	<b>111.</b> IL	→    <del>-</del> -=-	<u> </u>	<b>Ω</b>
ZJ-740TM-452	5	6	5.2	0.8-1.4	1.6-2.5	6-8	4200
ZJ-740TM-460	5	6	6.0	0.8-1.4	1.6-2.5	6-8	4200

4代表针,52、60代表针位, 选配--E: 抬压脚; A: 气动抬压脚,SX: 双差动,01代表单刀; 02代表双刀,N代表窄刀; W代表宽刀

4 represents the needle; 52 and 60 represent the needle positions

Optional Configurations: E: Presser Foot Lifter; A: Pneumatic Presser Foot Lifter, SX: Double Differential, 01: Single Knife; 02: Double Knife, N: Narrow Knife; W: Wide Knife